

Bench scale with plateau



Suitable for unpacked and packed meat

Pre-conditions

- Made of stainless steel
- Mono load cell is IP68 approved
- Height adjustable feet (+/- 50 mm)
- Overload safety on all four corners

Safety and legal requirements

To prevent intruding moisture and for the highest possible protection of the mono load cell, the load receptor is hermetic closed.

Calibration & legal for trade

Achieve guarantee for precise weighing and best price for meat with a service agreement, covering yearly maintenance, calibration and certification.

Service is performed by authorized and certified Frontmatec technicians and the scale is built with legal to trade components.

Options

Type	Dimensions (LxWxH) mm	Weighing capacity kg	Minimum load kg	Lowest readable value kg
5300000856 max. 30 kg	400x300x100	30	0.2	0.01
5300000855 max. 60 kg	500x400x750	60	0.4	0.02
4300013292	600x500x130	150	1	0.05
4300050716	600x500x700	30	0.2	0.01
		60	0.4	0.02
		150	1	0.05
4300037908	600x500x800	30	0.2	0.01
		60	0.4	0.02
		150	1	0.05
5300000862	600x500x900	30	0.2	0.01
		60	0.4	0.02
		150	1	0.05



Indicators

Especially designed for the meat industry the housing consists of stainless steel with a clear display, easy and logical to use and will provide a continuous read out of weighing data.

All indicators are as standard supplied with RS232, USB and Ethernet connection to remote computer system.



Avery ZM201, type 5300000871

- Water resistant (IP66)
- Height of display 13 mm
- No plug connections - waterproof wire transits
- Continuous read out of weighing data
- Including zero setting and tare



Avery ZM301, type 5300000870

- Waterproof (IP69K)
- Height of display 20 mm
- More display options (for example filling status bar)



Avery ZM303, type 5300000873

- Waterproof (IP69K)
- Height of display 20 mm
- More display options (for example filling status bar)
- Numeric key pad and extra function keys



Avery ZM405, type 5300006686

- Waterproof (IP69K)
- Height of display 20 mm
- More display options (for example filling status bar)
- Numeric key pad and extra function keys
- Programmable

AfterSales_V1-1_2021_EN

Contact

Central/Eastern Europe
Phone: +49 252 185 070
E-mail: as.ce@frontmatec.com

Central/Eastern Europe, Poland
Phone: +48 227 345 551
E-mail: as.ce@frontmatec.com

Northern Europe
Phone: +45 36 999 099
E-mail: as.ne@frontmatec.com

Southern Europe
Phone: +34 932 643 800
E-mail: as.se@frontmatec.com

Russia
Phone: +7 495 424 9559
E-mail: as.ru@frontmatec.com

Western Europe
Phone: +31 886 294 000
E-mail: as.we@frontmatec.com