



## SERVICE SOLUTIONS // SCALES

# SUITABLE FOR CRATES AND BOXES

### Pre-conditions

- Made of stainless steel
- Rollers of waterproof plastic with stainless steel ball bearings
- Mono load cell is IP68 approved
- Height adjustable feet (+/- 50 mm)
- Overload safety on all four corners

### Safety and legal requirements

To prevent intruding moisture and for the highest possible protection of the mono load cell, the load receptor is hermetic closed.

### Calibration & legal for trade

Achieve guarantee for precise weighing and best price for meat with a service agreement, covering yearly maintenance, calibration and certification.

Service is performed by authorized and certified Frontmatec technicians and the scale is built with legal to trade components..

### Options

Type	Dimensions (LxWxH) mm	Weighing capacity kg	Minimum load kg	Lowest readable value kg
5300000858	700x450x750	30	0.2	0.01
5300000864	700x450x830	60	0.4	0.02
5300000857	700x450x900	150	1	0.05
5300000860	700x550x700	30	0.2	0.01
		60	0.4	0.02
		150	1	0.05
5300000859	700x550x900	30	0.2	0.01
		60	0.4	0.02
		150	1	0.05



## Indicators

Especially designed for the meat industry the housing consists of stainless steel with a clear display, easy and logical to use and will provide a continuous read out of weighing data.

All indicators are as standard supplied with RS232, USB and Ethernet connection to remote computer system.



### Avery ZM201, type 5300000871

- Water resistant (IP66)
- Height of display 13 mm
- No plug connections - waterproof wire transits
- Continuous read out of weighing data
- Including zero setting and tare



### Avery ZM301, type 5300000870

- Waterproof (IP69K)
- Height of display 20 mm
- More display options (for example filling status bar)



### Avery ZM303, type 5300000873

- Waterproof (IP69K)
- Height of display 20 mm
- More display options (for example filling status bar)
- Numeric key pad and extra function keys



### Avery ZM405, type 5300006686

- Waterproof (IP69K)
- Height of display 20 mm
- More display options (for example filling status bar)
- Numeric key pad and extra function keys
- Programmable

## CONTACT

Central/Eastern Europe  
+49 252 185 070  
service.de@frontmatec.com

Northern Europe, Kolding  
+45 36 999 099  
service.kol.dk@frontmatec.com

Northern Europe, Tandslet  
+48 227 345 551  
service.tan.dk@frontmatec.com

Southern Europe  
+34 932 643 800  
service.es@frontmatec.com

Western Europe  
+31 886 294 000  
service.nl@frontmatec.com