



SERVICE SOLUTIONS // SCALES

FOR THE INTAKE OR DISPATCH AREA

To ensure compliance and accuracy in the weighing of pallets, drums or boxes ensuring precision in payment.

Pre-conditions

- Made of stainless steel
- With four waterproof stainless steel load cells (IP67)
- Easily installed
- Suitable in a foundation pit

Safety and legal requirements

To ensure easy cleaning and low maintenance the floor scale is supplied with a stainless steel tear plate top which has two

protection of the mono load cell, the load receptor is hermetic closed

Calibration & legal for trade

Achieve guarantee for precise weighing and best price for meat with a service agreement, covering yearly maintenance, calibration and certification.

Service is performed by authorized and certified Frontmatec technicians and the scale is built with legal to trade components.

| Type | Dimensions (LxWxH) mm | Weighing capacity kg | Minimum load kg | Lowest readable value kg |
|-------------------------|-----------------------|----------------------|-----------------|--------------------------|
| 5300000850 | 1500x1500 | 1500 | 10 | 0.5 |
| 5300000848 pitframe | 1500x1500x120 | 2000 | 20 | 1 |
| 5300000851 | 2000x1500 | 1500 | 10 | 0.5 |
| | | 2000 | 20 | 1 |
| 5300000852 pitframe | 2000x1500x120 | 1500 | 10 | 0.5 |
| | | 2000 | 20 | 1 |
| 5300000846 max. 1500 kg | 1250x1250x80 | 1500 | 10 | 0.5 |
| | | 2000 | 20 | 0.1 |
| 5300000847 access plate | 1250x900x80 | 1500 | 10 | 0.5 |
| | | 2000 | 20 | 1 |
| 4300022564 max. 1500 kg | 1250x1250x40 | 1500 | 10 | 0.5 |
| | | 2000 | 20 | 1 |



Indicators

Especially designed for the meat industry the housing consists of stainless steel with a clear display, easy and logical to use and will provide a continuous read out of weighing data.

All indicators are as standard supplied with RS232, USB and Ethernet connection to remote computer system.



Avery ZM201, type 5300000871

- Water resistant (IP66)
- Height of display 13 mm
- No plug connections - waterproof wire transits
- Continuous read out of weighing data
- Including zero setting and tare



Avery ZM301, type 5300000870

- Waterproof (IP69K)
- Height of display 20 mm
- More display options (for example filling status bar)



Avery ZM303, type 5300000873

- Waterproof (IP69K)
- Height of display 20 mm
- More display options (for example filling status bar)
- Numeric key pad and extra function keys



Avery ZM405, type 5300006686

- Waterproof (IP69K)
- Height of display 20 mm
- More display options (for example filling status bar)
- Numeric key pad and extra function keys
- Programmable

CONTACT

Central/Eastern Europe
+49 252 185 070
service.de@frontmatec.com

Northern Europe, Kolding
+45 36 999 099
service.kol.dk@frontmatec.com

Northern Europe, Tandslet
+48 227 345 551
service.tan.dk@frontmatec.com

Southern Europe
+34 932 643 800
service.es@frontmatec.com

Western Europe
+31 886 294 000
service.nl@frontmatec.com