



SERVICE SOLUTIONS // SCALES

FOR THE INTAKE AREA, CUTTING FLOOR OR DISPATCH AREA

To ensure smooth operation with precise product weighing and exact position of the weighing section two V-blocks are welded onto the existing tube rail.

Pre-conditions

- The static tube scale made of stainless steel consist of a weighing section and a weighing part
- Load cells are IP66 approved
- Suitable on most rail works
- Easily mounted

Safety and legal requirements

For highest possible protection against dirt and moisture, the two load cells are mounted above the conveyor between two U-profiles in the weighing section. It is designed to meet the strictest demand on health and safety.

Calibration & legal for trade

Achieve guarantee for precise weighing and best price for meat with a service agreement, covering yearly maintenance, calibration and certification.

Service is performed by authorized and certified Frontmatec technicians and the scale is built with legal to trade components.

Options

Type	Lenght mm	Tube diameter mm	Weighing capacity kg	Minimum load kg	Lowest readable value kg
5300001217	320	60	300	2	0.1
5300000355	668	60	300-600	2-4	0.1-0.2
5300000355	668	48	300	2	0.1
5300000356	928	60	600-800	4	0.2
5300001218	1100	60	600-800	4	0.2



Indicators

Especially designed for the meat industry the housing consists of stainless steel with a clear display, easy and logical to use and will provide a continuous read out of weighing data

All indicators are as standard supplied with RS232, USB and Ethernet connection to remote computer system.



Avery ZM201, type 5300000871

- Water resistant (IP66)
- Height of display 13 mm
- No plug connections - waterproof wire transits
- Continuous read out of weighing data
- Including zero setting and tare



Avery ZM301, type 5300000870

- Waterproof (IP69K)
- Height of display 20 mm
- More display options (for example filling status bar)



Avery ZM303, type 5300000873

- Waterproof (IP69K)
- Height of display 20 mm
- More display options (for example filling status bar)
- Numeric key pad and extra function keys



Avery ZM405, type 5300006686

- Waterproof (IP69K)
- Height of display 20 mm
- More display options (for example filling status bar)
- Numeric key pad and extra function keys
- Programmable

CONTACT

Central/Eastern Europe
+49 252 185 070
service.de@frontmatec.com

Northern Europe, Kolding
+45 36 999 099
service.kol.dk@frontmatec.com

Northern Europe, Tandslet
+48 227 345 551
service.tan.dk@frontmatec.com

Southern Europe
+34 932 643 800
service.es@frontmatec.com

Western Europe
+31 886 294 000
service.nl@frontmatec.com